

Hamlet

2D BARCODE SCANNER

FOR LINEAR & QR CODES
WIRELESS

INDUSTRIAL
2D
WIRELESS



INDUSTRIAL

HBCS2D100W

Hamlet HBCS2D100W è un lettore di codici QR e lineari Industriale Bluetooth ideale per il punto vendita e la logistica. La tecnologia di scansione 2D imaging offre ottime prestazioni e precisione di lettura per QR code bidimensionali e codici a barre di tipo lineare come EAN e UPC. La leggerezza e il design ergonomico permettono un utilizzo prolungato senza fatica. Il barcode scanner HBCS2D100W è dotato di batteria al litio da 2200 mAh che consente un utilizzo prolungato senza bisogno di ricarica. La batteria si ricarica tramite una normale porta USB col cavo fornito in dotazione.

LIGHT SOURCES: 617NM LED AIMER, WHITE LED
SUPPORTED SYMBOLOGIES: 1D: CODEBAR, CODE 11, CODE 39/CODE 93, UPC/EAN, CODE 128/EAN128, INTERLEAVED 2 OF 5, MATRIX 2 OF 5, MSI CODE, INDUSTRIAL 2 OF 5, GS1 DATABAR; 2D: QR CODE, DATA MATRIX, PDF417
SCAN TYPE: IMAGE CMOS
SCAN SPEED: >25INCH/63CM PER SECOND
SCAN METHOD: MANUAL/AUTOMATIC/SUCCESSIVE SCANNING
SCAN ANGLE: YAW 65°, ROTATION 360°, PITCH 60°
PRECISION: CODE 39 4.8 MIL, UPC60% 5 MIL, PDF417 5 MIL, DATAMATRIX 7.5 MIL - DEPTH OF SCAN FIELD: 5-390MM
ERROR RATE: LESS THAN 1/5 MILLION
INTERFACE: USB-HID, USB-COM, RS232 (ONLY USB CABLE INCLUDED)

WORKING FREQUENCY: BLUETOOTH V2.1 + EDR (CLASS 1)
TRANSMISSION DISTANCE: ≤100 M (OPEN YARD)
STORAGE ABILITY: 512000 BYTES
PAIRING MODEL: ONE TO ONE
RECEIVING END: BLUETOOTH USB ADAPTER
DIMENSIONS: 102 x 72 x 177 MM - WEIGHT: 250 G
MATERIAL: ABS+PC - CABLE LENGTH: 2 M
OPERATING TEMP.: -20°C~60°C - STORAGE TEMP.: -40°C~70°C
RELATIVE HUMIDITY : 5%~95% (NON-CONDENSING)
CHARGING TIME: 5H
LITHIUM BATTERY: 2200 MA - VOLTAGE: DC5V± 5%
OPERATING CURRENT: 135MA - STANBY CURRENT: 2MA
CHARGING MODE: MINI USB



CONTENUTO DELLA SCATOLA

- Barcode Scanner 2D Industriale Bluetooth
- Ricevitore wireless USB
- Cavo di ricarica
- Alimentatore
- Manuale d'uso



hamletcom.com