

# Hamlet

## 2D BARCODE SCANNER

FOR LINEAR & QR CODES  
USB CABLE 2M



DISPLAY CODE

INDUSTRIAL  
2D  
USB CABLE

INDUSTRIAL

HBCS2D300U

Hamlet HBCS2D300U è un lettore di codici QR e lineari Industriale ideale per supermercati e magazzini di medie dimensioni con un elevato carico di lavoro. La tecnologia di scansione 2D imaging offre elevate prestazioni e precisione di lettura per i codici bidimensionali come i codici QR e i codici a barre lineari come EAN e UPC. La leggerezza e il design ergonomico permettono un utilizzo prolungato senza fatica. Lo stand in dotazione offre un pratico appoggio per avere sempre lo scanner a portata di mano e può essere utilizzato anche per effettuare scansioni a mani libere. Il barcode scanner HBCS2D300U è dotato di cavo USB con lunghezza di 2 metri.

LIGHT SOURCES: 617NM LED AIMER, WHITE LED  
SUPPORTED SYMBOLOGIES: 1D:UPC/EAN,UPC/EAN WITH SUPPLEMENTALS, BOOKLAND EAN, ISSN,UCC COUPON EXTENDED CODE, CODE 128, GSI-128, ISBT 128, CODE39, CODE93 FULL ASCII, TRIOPTIC CODE39, CODE32, CODE11, MATRIX 2 OF 5, LNTERLEAVED 2 OF 5, DISCRETE 2 OF 5, CODEBAR, MSI, CHINESE 2 OF 5, GSI DATABAR VARIANTS, KOREAN 3 OF 5, ISBT CONCAT. 2D: PDF417, MICROPDF417, COMPOSITE CODES, TLC-39, DATA MATRIX, MAXI CODE, QR CODE, MICRO QR, AZTEC  
SCAN TYPE: IMAGE CMOS  
SCAN SPEED: >25INCH/63CM PER SECOND  
SCAN METHOD: MANUAL/SUCCESSIVE SANNING (OPTIONAL)

SCAN ANGLE: YAW 60°, ROTATION 360°, PITCH 60°  
PRECISION: SR: CODE 39 4.8MIL, UPC60%, 5MIL, PDF417 5MIL, DATAMATRIX 7.5MIL  
DEPTH OF SCAN FIELD: 5-390MM  
ERROR RATE: LESS THAN 1/5MILLION  
INTERFACE: USB-HID, USB-COM, RS232 (ONLY USB CABLE INCLUDED)  
DIMENSIONS: 102MM\* 72MM\* 177MM - WEIGHT: 250G  
MATERIAL: ABS+PC - CABLE LENGTH: 2M  
OPERATING TEMPERATURE: -20°C~50°C  
STORAGE TEMPERATURE: -40°C~70°C  
RELATIVE HUMIDITY : 0%~95% (NON CONDENSING)  
VOLTAGE: DC5V± 1%  
CURRENT: 400MA



### CONTENUTO DELLA SCATOLA

- Barcode Scanner 2D Industriale USB
- Cavo USB/RJ45 (2 m)
- Base di supporto
- Manuale d'uso

hamletcom.com